



THORENS TP 92

Precision tonearms 9"/10"/12"

| Specifications | | | |
|---------------------------------|--|--|--|
| | TP 92 9" | TP 92 10" | TP 92 12" |
| Length | 9" | 10" | 12" |
| Mounting distance | 215mm | 237,8mm | 291,4mm |
| effective lenght | 232,8mm | 254mm | 304,8mm |
| Overhang | 17,8mm | 16,2mm | 17,8mm |
| Angular offset | 23,66° | 21,6° | 17,8° |
| Inner null | 66,0mm | 66,0mm | 66,0mm |
| Outer null | 120,9mm | 120,9mm | 120,9mm |
| effective mass | 11g | 14g | 21g |
| Max distortion between 0-points | 0,63% | 0,38% | 0,46% |
| Geometry | Baerwald/Loefgren „A“ | Baerwald/Loefgren „A“ | Baerwald/Loefgren „A“ |
| Bearing | Cardanic | Cardanic | Cardanic |
| Weight | 360g | 415g | 465g |
| Connector | lose cables or Mini DIN (OEM II-Version) | lose cables or Mini DIN (OEM II-Version) | lose cables or Mini DIN (OEM II-Version) |
| Drilling | 18mm dia | 18mm dia | 18mm dia |
| Antiskating | ferrit magnets, friction free | ferrit magnets, friction free | ferrit magnets, friction free |
| EAN Code | 4260270220010 4260270220027 | 4260270221185 4260270221192 | 4260270220980 4260270221208 |